



Male plug-in connector - Side-by-side version - Pitch 10,16mm - 02 ÷ 12 poles

GENERAL INFORMATION

pitch:	10,16 mm
housing height:	12,20 mm
housing depth:	8.5 mm
dimensional class:	medium
wire section:	-
clamp opening size:	-
wire stripping:	-
operating temperature:	-40°C ÷ +13°C

ELECTRICAL CHARACTERISTICS

current:	15A
voltage:	500V
impulse voltage:	6 kV

MECHANICAL CHARACTERISTICS

-	-
---	---

APPROVALS DATA



EN 61984

current: 15A

voltage: 500V

FILE: CA02.04178



EN 61984

15A

500V

40005779



UL 1059

12A factory / 12A field

600V

E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	n/a
clamp/spring:	n/a

AVAILABLE COLOURS



other colours:

upon request

terminal:

Tin-plated copper alloy

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
02	PV02-10,16-V	N/A	N/A	N/A
03	PV03-10,16-V	N/A	N/A	N/A
04	PV04-10,16-V	N/A	N/A	N/A
05	PV05-10,16-V	N/A	N/A	N/A
06	PV06-10,16-V	N/A	N/A	N/A
07	PV07-10,16-V	N/A	N/A	N/A
08	PV08-10,16-V	N/A	N/A	N/A
09	PV09-10,16-V	N/A	N/A	N/A
10	PV10-10,16-V	N/A	N/A	N/A
11	PV11-10,16-V	N/A	N/A	N/A
12	PV12-10,16-V	N/A	N/A	N/A