



Male plug-in connector - Vertical - Dual row - Staggered - Modular version - Pitch 5,08mm - 02÷03 poles

GENERAL INFORMATION

| | |
|------------------------|----------------|
| pitch: | 5,08 mm |
| housing height: | 22,00 mm |
| housing depth: | 23.74 mm |
| dimensional class: | medium |
| wire section: | - |
| clamp opening size: | - |
| wire stripping: | - |
| operating temperature: | -40°C ÷ +130°C |

ELECTRICAL CHARACTERISTICS

| | |
|------------------|------|
| current: | 12A |
| voltage: | 250V |
| impulse voltage: | 4 kV |

MECHANICAL CHARACTERISTICS

APPROVALS DATA



EN 61984

| | |
|----------|------------|
| current: | 12A |
| voltage: | 250V |
| FILE: | CA02.04178 |



EN 61984

| | |
|----------|----------|
| current: | 12A |
| voltage: | 250V |
| FILE: | 40005779 |



UL 1059

| | |
|----------|-------------------------|
| current: | 12A factory / 12A field |
| voltage: | 300V |
| FILE: | E178356 |

MATERIALS

| | |
|----------|---------------|
| housing: | PA - UL 94 V0 |
|----------|---------------|

AVAILABLE COLOURS

screw:
clamp/spring:
terminal:

n/a



n/a

other colours:

upon request

Tin-plated copper alloy

| poles | P/N | pcs/pack | W [Kg]* | W [Kg]* |
|-------|---------------|----------|---------|---------|
| 02 | PDSV02-5,08-V | N/A | N/A | N/A |
| 03 | PDSV03-5,08-V | N/A | N/A | N/A |