



DIN rail mounting Female plug-in connector - Side-by-side - Stackable version - Pitch 5mm - 03 ÷ 12 poles

GENERAL INFORMATION

pitch:	5 mm
housing height:	17,00 mm
housing depth:	20.1 mm
dimensional class:	medium
wire section:	2.5 mm ² / 14 AWG
clamp opening size:	2.8 × 3.1 mm
wire stripping:	max 9 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	12A
voltage:	250V
test voltage:	4 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5 Nm / 4.5 in.lbs

APPROVALS DATA



current:	-	-	UL 1059
voltage:	-	-	12A factory / 12A field
wire section:	-	-	300V
torque:	-	-	14÷30AWG
FILE:	-	-	4,5Lb-in
			E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel
clamp/spring:	Nickel copper alloy
terminal:	Tin-plated copper alloy

AVAILABLE COLOURS

GN (STD)	GY	BK	BL	RD	YL	OG
other colours:						upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
03	SVR03-5-DR	N/A	N/A	N/A

04	SVR04-5-DR	N/A	N/A	N/A
05	SVR05-5-DR	N/A	N/A	N/A
06	SVR06-5-DR	N/A	N/A	N/A
07	SVR07-5-DR	N/A	N/A	N/A
08	SVR08-5-DR	N/A	N/A	N/A
09	SVR09-5-DR	N/A	N/A	N/A
10	SVR10-5-DR	N/A	N/A	N/A
11	SVR11-5-DR	N/A	N/A	N/A
12	SVR12-5-DR	N/A	N/A	N/A